

APPLICATION *GUIDE*

TOEPASSINGSGIDS

VERSION 21.4 WEERGAWE



www.leadertread.co.za



info@leadertread.co.za



011 473 8200



8 Kelvin Street
Industria
Johannesburg

SABS
ISO 9001



LEADER RUBBER COMPANY
SOUTH AFRICA (PTY) LTD



**LEADER
TREAD**TM
leading the way[®]



	All POSITION ALLE POSISIE			DRIVE DRYF			TRAILER & SUPER SINGLE SLEEPWA & SUPER ENKEL		
 Long Haul / Lang Afstand	MM90 	MM86 		MM1 	MM43 	MM80 	MM84 WING 	MM79 WING 	MM61 
 Regional / Plaaslike	MM90 	MM86 		MM1 	MM43 	MM80 	MM90 	MM89 WING 	MM84+ WING 
 City & Intercity / Stad & Intercity	MM90 	MM86 		MM1 	MM43 	MM80 	MM90 	MM89 WING 	MM84+ WING 
 On/Off Op / Af	MM90 	MM86 	MM38 	MM75 	MM7 		MM90 	MM84+ WING 	
 Off Road / Grond Pad	MM90 	MM86 	MM38 	MM75 	MM65 	MM7 	MM90 	MM84+ WING 	
 Light Truck Ligte Vragmotor	MM84 								

	All POSITION ALLE POSISIE			DRIVE DRYF			TRAILER & SUPER SINGLE SLEEPWA & SUPER ENKEL		
 Long Haul / Lang Afstand	M38 	M90 Light 		M88 	M43 		M38 	M3 	
 Regional / Plaaslike	M38 	M90 Light 		M43 			M38 	M3 	
 City & Intercity / Stad & Intercity	M38 	M90 Light 		M43 			M38 		
 On/Off Op / Af	M38 	M90 Light 		M88 	M36 	M7 	M78 WING 		
 Off Road / Grond Pad	M38 			M36 	M7 		M38 		
 Light Truck Ligte Vragmotor	M3 			M17 	M3 		M3 		

TYRE SIZES - TREAD WIDTHS

BANDE GROOTTE - TREAD BREEDTE

Size	 Min Width	 Max Width	 Buffed Circumference
6.50-16	140	150	2350
7.00-16	140	160	2400
7.00R16	140	160	2400
7.50-16	140	170	2450
7.50R15	165	165	2450
7.50R16	140	170	2450
8.25-16	150	176	2950
8.25-20	160	176	2950
8.25R16	165	180	2600
8.25R20	165	176	2950
8.5R17.5	150	165	2600
8.5R20	165	165	2950
9.00-20	176	200	3050
9.00R20	176	200	3075
9.00R22.5	176	176	2950
10.00-20	190	220	3150
10.00R15	190	190	2700
10.00R17.5	165	176	2600
10.00R20	180	220	3200
10.00R22.5	176	230	3200
11.00-20	200	230	3250
11.00-22.5	210	220	3200
11.00R20	200	220	3285
11.00R22.5	220	240	3270
11.00R24.5	210	230	3200
11R22.5	200	240	3270
12.00R20	220	250	3390
12.00-20	230	260	3270
12/70R18	230	230	3270
12R22.5	210	260	3280

Size	 Min Width	 Max Width	 Buffed Circumference
12.00R24	215	230	3660
205/75R17.5	165	180	2300
215/75R17.5	170	210	2350
225/70R19.5	180	210	2350
235/75R15	180	210	2450
235/75R17.5	180	230	2415
245/70R17.5	200	230	2415
265/70R17.5	210	220	2480
265/70R16	220	230	2750
225/75R19.5	180	190	2515
225/70R19.5	180	190	2475
235/70R19.5	190	200	2495
245/70R19.5	200	220	2555
265/70R19.5	210	240	2750
275/70R17.5	230	230	2950
275/70R22.5	210	255	2950
285/60R22.5	240	260	2950
285/70R19.5	210	250	2750
295/60R22.5	240	280	3100
295/70R22.5	240	280	3270
295/80R22.5	240	280	3250
305/80R22.5	240	280	3270
305/80R22.5	240	240	3270
13R22.5	230	270	3410
315/60R22.5	240	280	3270
315/70R22.5	240	290	3270
315/80R22.5	240	290	3275
385/65R22.5	295	305	3270
425/65R22.5	320	330	3440
445/65R22.5	320	360	3490